



## TRIPLE QX SYNPLUS VAG 5W30 SYNTHETIC

Document version: December 11th 2023



### Description

This TQX SYNPLUS VAG 5W30 synthetic lubricant is designed for VAG engines where the VW 504.00/ 507.00 specification is required. It is also designed to meet specifications of other OEM's and reaches ACEA and API requirements by balancing excellent fluidity with advanced engine protection, regardless of the driving conditions.

### Performance-level

ACEA C3  
API SN  
BMW LL-04<2019  
MB 229.51  
Porsche C30  
VW 504.00 / 507.00

### Packing units

ART.NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521776092	1 L	12	-
TQX.521776091	5 L	4	-
TQX.521776095	20 L	1	-
TQX.521776099	60 L	1	12
TQX.521771656	199 L	1	-

## Typicals

TEST	VALUE	
Density at 15°C	0.856	kg/l
Kinematic Viscosity at 40°C	68.0	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	11.7	mm <sup>2</sup> /s
Viscosity Index	169	
Flashpoint COC	230	°C
Pourpoint	-39	°C
Total Base Number	6.6	mgKOH/g
Sulphated Ash	0.7	mass%